

KEL-BERG®

TRAILERS SVERIGE AB

LASTAS

HOVEDINDGANG

Udlevering

KLA

TEL: +46 070-536 3939

WEB: www.kelberg.se



MODEL
D540V

KEL-BERG 3-AXLE 10.500 MM
FLATBED TRAILER

SPECIFICATION FOR D540V

KEL-BERG 3-AXLE 10.500 MM FLATBED TRAILER

WEIGHTS & MEASURES:

Total length	12.150-13.050 mm
Drawbar length	1.670-2.570 mm
Front overhang	745 mm
Rear overhang	1.645 mm
Coupling height	650 mm
Width	2.600 mm
Load height	1.100 mm
Axle distance	6.280/1.810 mm

Speed	90 km/h
Front axle pressure	10.000 kg
Rear axle load	20.000 kg
Total weight	30.000 kg
Service weight	6.800 kg

CHASSIS:

Made of heavy duty main frame, welded steel construction with 57mm VBG multi drag.



SPECIFICATION FOR D540V

KEL-BERG 3-AXLE 10.500 MM FLATBED TRAILER

BODY:

Heavy-duty, welded, high-strength steel construction
10 pairs of anchorage points in edge line 5t
6 pairs of LAXO sleeves in edge line
6 pairs of LAXO sleeves in the centre
4 ladders
Front height 1.100mm
Heavy duty welded steel construction with extra strong cross beams.
Edge line of bent steel plate.
4 handrails each side 800mm, with cheek grip posts K20
Rear doors 800mm with cheek grip posts K20
28mm hardwood bottom

AXLES:

3 x 10ton SAF axles with disc brakes
3rd axle liftable
Air suspension with level valve manoeuvrable front and rear.
With ABS, EBS
3rd axle liftable, manoeuvrable from cab and with load sensing valve

WHEELS:

12 pcs 265/70R19.5 mounted on steel rim with tyres

BRAKING:

2-circuit compressed air system with EBS and ABS,
Spring brake bells for parking brake
1 pc duomatic red/yellow



SPECIFICATION FOR D540V

KEL-BERG 3-AXLE 10.500 MM FLATBED TRAILER

ELECTRICAL SYSTEM:

24 Volts according to current regulations
2 x multi-chamber rear lights
Diode type side/position lights
2 x Halogen rear lights at the rear

ELECTRICAL CONNECTORS:

1 x 14-pin connector for lighting

PAINTING:

Colour:

OTHER:

Red/white reflective signs (ECE70) at the rear
Yellow reflective (ECE104) side and rear contour markings
Fenders with anti-spray
2 stainless steel toolboxes - 1000*500*480*2mm

SUPPLEMENTS AGAINST STD :

2 pcs Work lights LED at the light boom
2 pcs Work lights LED at shaft 2-3

OPTIONS:

Aluminium wheels

