

TEL: +46 070-536 3939 WEB: www.kelberg.se



MODEL C650K **KEL-BERG 5-AXLE 5-AXLE 12,220 MM CONTAINER CHASSIS 44 TON**

SPECIFICATION FOR C650K

KEL-BERG 5-AXLE 5-AXLE 12,220 MM CONTAINER CHASSIS 44 TON

WEIGHTS & MEASURES:

Overall length Flap length Drawbar length Front overhang Rear overhang Coupling height Width Load height Axle distance

14.692 mm 12,220 mm - 2,600 mm 2,600 mm - 3,400 mm 1,460 mm - 1,600 mm 1,600 mm - 3,400 mm 650 mm (16.5 in) 2,300 mm - 3,400 mm 1,151 mm / 4,560 mm / 1,320 mm 1,810mm / 4,560mm / 1,320mm / 1,320mm

Speed King pin pressure Rear axle pressure Total weight Service weight

90 km/h 20.000 kg 24.000 kg 44.000 kg 7.000 kg

CHASSIS:

Manufactured with heavy-duty main frame, welded steel construction with 57mm Drawbar type 2024 from Trailerkomponenter AB.

CONTAINERS: 2 x 5.600 - 6.000mm container

WHEELS: 20pcs 265/70 R19,5 mounted on steel rim. M+S













PAGE: 2

WWW.KELBERG.SE | +46 070-536 3939 | 253 68, HELSINGBORG

Whilst every effort has been made to ensure that the information in this specification sheet is accurate, some errors may occur. It is important that you do not rely solely on this information, but that you check with your dealer any items that you believe will affect your decision to purchase this vehicle. Kel-Berg Trailers Sverige AB, accepts no responsibility for loss or damage resulting from incorrect or misleading information. This specification is for guidance only and does not constitute an offer of sale or warranty of the specification of this vehicle. All specifications are subject to change without notice and/or verification E&OE

SPECIFICATION FOR C650K

KEL-BERG 5-AXLE 5-AXLE 12,220 MM CONTAINER CHASSIS 44 TON

AXLES:

5 x 10 tonne BPW axles with disc brakes 3 + 5 axle liftable pin 10 + 11 VBG Air suspension with level valve operated front and rear. With ABS, EBS 2pcs weight bell

BRAKING:

2-circuit compressed air system with EBS and ABS, Spring brake bells for parking brake Duomatic red/yellow

ELECTRICAL SYSTEM:

24 Volts according to current regulations 2 x multi-chamber rear LED lights Side/position lights of diode type LED 4 pcs rear lights LED

ELECTRICAL CONNECTORS:

1 x 14-pin plug for lighting

PAINTING:

3 layers of base coat with zinc primer 2 component surface coating Colour: 1042 Chassis Grey













PAGE: 3

WWW.KELBERG.SE | +46 070-536 3939 | 253 68, HELSINGBORG

Whilst every effort has been made to ensure that the information in this specification sheet is accurate, some errors may occur. It is important that you do not rely solely on this information, but that you check with your dealer any items that you believe will affect your decision to purchase this vehicle. Kel-Berg Trailers Sverige AB, accepts no responsibility for loss or damage resulting from incorrect or misleading information. This specification is for guidance only and does not constitute an offer of sale or warranty of the specification of this vehicle. All specifications are subject to change without notice and/or verification. E&OE.

SPECIFICATION FOR C650K

KEL-BERG 5-AXLE 5-AXLE 12,220 MM **CONTAINER CHASSIS 44 TON**

OTHER:

Red/white reflective signs (ECE70) Screens with anti-spray P-light - Optional Aluminium rim Alcoa Durabright - Optional Power box left side included with Kapell BLACK 1x Toolbox

















PAGE: 4

WWW.KELBERG.SE | +46 070-536 3939 | 253 68, HELSINGBORG

Whilst every effort has been made to ensure that the information in this specification sheet is accurate, some errors may occur. It is important that you do not rely solely on this information, but that you check with your dealer any items that you believe will affect your decision to purchase this vehicle. Kel-Berg Trailers Sverige AB. accepts no responsibility for loss or damage resulting from incorrect or misleading information. This specification is for guidance only and does not constitute an offer of sale or warranty of the specification of this vehicle. All specifications are subject to change without notice and/or verification. E&OE.