



MODEL
T660K

KEL-BERG 5-AXLE 42T DRAWBAR
TIPPER TRAILER 32 M³

SPECIFICATION FOR T660K

KEL-BERG 5-AXLE 42T DRAWBAR TIPPER TRAILER 32 M³

WEIGHTS & MEASURES:

Total length	13,730/14,530 mm
Drawbar length	3,400/4,200 mm bolt
Front overhang	595 mm
Rear overhang	540 mm
Coupling height	650 mm
Width	2,550 mm
Axle distance	1,310 / 4,685 / 1,310 / 1,310 mm

TRAILER DIMENSIONS:

Internal length	9,575 mm
Internal width	2,440 mm
Height inside	1,350 mm
Cubic capacity	32
Tipping angle	46 degrees

Speed	90 km/h
Front axle pressure	18.000 kg
Rear axle load	24.000 kg
Total weight	42.000 kg
Service weight	9.000 kg

CHASSIS:

Made of heavy duty main frame, welded steel construction with Trako pulls.



SPECIFICATION FOR T660K

KEL-BERG 5-AXLE 42T DRAWBAR TIPPER TRAILER 32 M³

TIP PLATE:

Aluminims body
Approx. 32 m³
7 mm starch Aluminium bottom
5 mm thick Aluminium sides
Tipping cylinder mounted at the front
Air-operated hatch at the rear

AXLES:

2 x 9 ton BPW axles with front disc brakes
3 x 9 ton BPW axles with rear disc brakes
Front and rear air suspension with level valve control.
With ABS, EBS
Axle 3 & 5 liftable, manoeuvrable from cab (Pin 10+11)

WHEELS:

20 pcs 265 /70R19.5 M+S mounted on Aluminium Alcoa Dura-bright rims

BRAKING:

2-circuit compressed air system with EBS and ABS,
Spring brake bells for parking brake
1 pc duomatic red/yellow



SIDA: 3

WWW.KELBERG.SE | +46 070-536 3939 | 253 68, HELSINGBORG

Whilst every effort has been made to ensure that the information in this specification sheet is accurate, some errors may occur. It is important that you do not rely solely on this information, but that you check with your dealer any items that you believe will affect your decision to purchase this vehicle. Kel-Berg Trailers Sverige AB. accepts no responsibility for loss or damage resulting from incorrect or misleading information. This specification is for guidance only and does not constitute an offer of sale or warranty of the specification of this vehicle. All specifications are subject to change without notice and/or verification. E&OE.

SPECIFICATION FOR T660K

KEL-BERG 5-AXLE 42T DRAWBAR TIPPER TRAILER 32 M³

ELECTRICAL SYSTEM:

24 Volts according to current regulations
3 x 3 multi-chamber rear LED lights
6 LED work lights
2 work lights in tipping bucket
Side marking lamps in the bowl on each side

ELECTRICAL CONNECTORS:

1 x 14-pin connector for lighting

PAINTING:

Chassis colour:
Colour of tipper box:

OTHER:

Rear reflective signs (ECE70)
Red/white contour markings sides and rear
Fenders with anti-spray
2 pcs weight clocks
2 pcs rear flashing lights - active with reverse light
1 large Kelberg rear mudguard.
Plastic on rear undertray

OPTIONS:

Aluminium bale 45m³
Plastic in bottom + sides
Automatic canopy from Flip Top on remote Pneumatic
Optional RAL on canopy

