

KEL-BE

TEL: +46 070-536 3939 WEB: www.kelberg.se

MODEL T650K **KEL-BERG 4-AXLE 38T DRAWBAR TIPPER TRAILER 44 M³**

KEL-BERG

KEL-BERG

SPECIFICATION FOR T650K

KEL-BERG 4-AXLE 38T DRAWBAR TIPPER TRAILER 44 M³

WEIGHTS & MEASURES:

Total length Drawbar length Front overhang Rear overhang Coupling height Width Axle distance 13,380 / 15,080 / 15,600 mm 3,200 / 4,900 / 5,400 mm 770 mm 1,350 mm 650 mm 2,550 mm 1,310 / 4,940 / 1,810 mm

BODY DIMENSIONS:

Internal length Internal width Height inside Cubic Capacity Tipping angle Speed Front axle pressure Rear axle load Total weight Service weight

46 degrees 90 km/h 18,000 kg 20,000 kg 38,000 kg

8.000 kg

8.900 mm

2.440 mm

1.350 mm

30

CHASSIS:

Made with heavy duty main frame, welded steel construction with 57mm VBG multi drawbar.













SIDA: 2

WWW.KELBERG.SE | +46 070-536 3939 | 253 68, HELSINGBORG

Whilst every effort has been made to ensure that the information in this specification sheet is accurate, some errors may occur. It is important that you do not rely solely on this information, but that you check with your dealer any items that you believe will affect your decision to purchase this vehicle. Kel-Berg Trailers Sverige AB, accepts no responsibility for loss or damage resulting from incorrect or misleading information. This specification is for guidance only and does not constitute an offer of sale or warranty of the specification of this vehicle. All specifications are subject to change without notice and/or verification. BQOE.

SPECIFICATION FOR T650K

KEL-BERG 4-AXLE 38T DRAWBAR TIPPER TRAILER 44 M³

BODY:

Supplied with aluminium body 7 mm floor 5 mm sides Air operated locking hatch

AXLES:

2 x 9 tonne BPW axles with front drum brakes 2 x 10 tonne BPW axles with rear drum brakes Front and rear air suspension with level valve control. With ABS, EBS 4th axle liftable, manoeuvrable from cab (Pin 10)

WHEELS:

1+2 axle 385/55R22.5 mounted on Alcoa Dura Bright wheels 3+4 axle 385/65R22.5 mounted on Alcoa Dura Bright wheels

BRAKING:

2-circuit compressed air system with EBS and ABS, Spring brake bells for parking brake 1 pc duomatic red/yellow

ELECTRICAL SYSTEM:

24 Volts according to current regulations
2 x 2 multi-chamber rear LED lights
4 pcs LED work lights
6 side lights on each side + 1 on drawbar













SIDA: 3

WWW.KELBERG.SE | +46 070-536 3939 | 253 68, HELSINGBORG

Whilst every effort has been made to ensure that the information in this specification sheet is accurate, some errors may occur. It is important that you do not rely solely on this information, but that you check with your dealer any items that you believe will affect your decision to purchase this vehicle. Kel-Berg Trailers Sverige AB. accepts no responsibility for loss or damage resulting from incorrect or misleading information. This specification is for guidance only and does not constitute an offer of sale or warranty of the specification of this vehicle. All specifications are subject to change without notice and/or verification FAOF

SPECIFICATION FOR T650K

KEL-BERG 4-AXLE 38T DRAWBAR TIPPER TRAILER 44 M³

ELECTRICAL CONNECTORS:

1 x 14-pin plug for lighting

PAINTING:

Chassis colour: RAL 1042 Chassis grey or any RAL. Colour tipper box: RAL 9006 Silver or any RAL. Canopy colour: any RAL

OTHER:

Red/white reflective signs (ECE70) at the rear White reflective (ECE104) side and rear contour markings Fenders with anti-spray 1 large split Kelberg mudguard in the rear

INCLUDED IN THE PRICE:

Plastic bottom and sides Flip Top pneumatic canopy on remote control Aluminium body is available with 3 doors on the side 600mm high.

COSTED OPTIONAL EXTRAS:

Sliding hitch approx. 35,000kr





SIDA: 4

WWW.KELBERG.SE | +46 070-536 3939 | 253 68, HELSINGBORG

Whilst every effort has been made to ensure that the information in this specification sheet is accurate, some errors may occur. It is important that you do not rely solely on this information, but that you check with your dealer any items that you believe will affect your decision to purchase this vehicle. Kel-Berg Trailers Sverige AB. accepts no responsibility for loss or damage resulting from incorrect or misleading information. This specification is for guidance only and does not constitute an offer of sale or warranty of the specification of this vehicle. All specifications are subject to change without notice and/or verification. EXOE.